

SLine441

Mode		FR (fullrange)		XO (crossover)	
Crossover High-Pass (Lo-Cut)	Frequency	60 Hz		100 Hz	
	Slope	18 dB/oct		18 dB/oct	
	Shape	Bessel		Bessel	
Crossover Low-Pass (Hi-Cut)	Frequency	20.000 Hz		20.000 Hz	
	Slope	12 dB/oct		12 dB/oct	
	Shape	Butterworth		Butterworth	
PEQ1 Low-shelf	Frequency	30 Hz		30 Hz	
	Slope	12 dB/oct		12 dB/oct	
	Gain	-30 dB		-30 dB	
PEQ2	Frequency	2691 Hz		2691 Hz	
	Gain	-4,3 dB		-4,3 dB	
	Q	10,3		10,3	
	= Bandwidth	0,14 oct		0,14 oct	
PEQ3	Frequency	7363 Hz		7363 Hz	
	Gain	-2,5 dB		-2,5 dB	
	Q	4,49		4,49	
	= Bandwidth	0,32 oct		0,32 oct	
PEQ4	Frequency	3296 Hz		3296 Hz	
	Gain	-2,8 dB		-2,8 dB	
	Q	6,55		6,55	
	= Bandwidth	0,22 oct		0,22 oct	
PEQ5	Frequency	339 Hz		339 Hz	
	Gain	-5,8 dB		-5,8 dB	
	Q	4,23		4,23	
	= Bandwidth	0,34 oct		0,34 oct	
PEQ6	Frequency	11045 Hz		11045 Hz	
	Gain	2,7 dB		2,7 dB	
	Q	3,5		3,5	
	= Bandwidth	0,41 oct		0,41 oct	
Limiter	Z(nom)	8 Ohm		8 Ohm	
	P(rms)	200 Watt		200 Watt	
	U(rms)	40 Volt		40 Volt	